



[11] Patent Number: 5,596,333

[45] **Date of Patent:** Jan. 21, 1997

- | | | | |
|-----------|---------|-------------------------|----------|
| 5,280,472 | 1/1994 | Gilhausen et al. . | |
| 5,365,516 | 11/1994 | Jandrell . | |
| 5,383,161 | 1/1995 | Sejnowski et al. | 67/134 |
| 5,392,454 | 2/1995 | Schwendeman et al. | 455/13.1 |
| 5,465,393 | 11/1995 | Frostrom et al. | 455/45.1 |
| 5,475,864 | 12/1995 | Hamabe | 455/33.1 |
| 5,491,833 | 2/1996 | Hamabe | 455/33.1 |

Primary Examiner—Thomas H. Tarcza

Assistant Examiner—Dao L. Phan

Attorney, Agent, or Firm—Daniel C. Crilly; Kevin A. Buford; Jeffrey G. Toler

[57] **ABSTRACT**

A communication system (100) employs a method (600) and apparatus (101) for conveying a communication signal between a communication unit (105) and a base site (101) that services a sectorized coverage area (103). The communication unit (105) transmits an uplink communication signal (113) to the base site (101). The base site (101) receives (603) the uplink communication signal (113) and determines (605) an approximate location of the communication unit (101) within a first portion (111) of a sector (108) of the sectorized coverage area (103). A downlink communication signal is then transmitted (609, 613) to the communication unit (105) based on the approximate location of the communication unit (105) using an antenna structure that produces a beamwidth (117) narrower than an angular width of the sector (108).

32 Claims, 6 Drawing Sheets

base
locator
narrower
beam

U.S. PATENT DOCUMENTS

4,101,836	7/1978	Craig et al.	325/302
4,128,740	12/1978	Graziano	179/2 EB
4,144,496	3/1979	Cunningham et al.	325/53
4,317,229	2/1982	Craig et al.	455/277
4,845,504	7/1989	Roberts et al.	342/457
5,134,715	7/1992	Parl et al.	455/64
5,235,633	8/1993	Dennison et al.	379/60

